

Fan		EDrive				Motor	
Model	Voltage (V)	Item #	Input Voltage (V)	Output Voltage (V)	Max Input Current (A)	Not Field Adjustable	Field Adjustable
RSV 400	3x208-240	321.0510.2200	3x200-240	3x200-240	5.6	-	200V (DELTA)
	3x380-420	321.0510.4200	3x380-480	3x380-480	3.5	-	400V (WYE)
RSV 450	3x208-240	321.0512.2200	3x200-240	3x200-240	8.9	-	200V (DELTA)
	3x380-420	321.0512.4200	3x380-480	3x380-480	5.6	-	400V (WYE)

Note:

The wire sizes shown are typical and may not apply to all jobs. This system must be installed in compliance with the NFPA 70 National Electric Code and/or any local codes.

—— Line Voltage ----- Low Voltage Signal

PROPRIETARY AND CONFIDENTIAL

The information contained in this drawing is the sole property of ENERVEX, Inc. Any reproduction in part or as a whole with out the express written consent of ENERVEX, Inc. is prohibited.

NOT TO SCALE

ENERVEX®
GREEN BEFORE GREEN WAS IN
1685 Bluegrass Lakes Pkwy
Alpharetta, GA 30004
(770)587-3238
Fax (770)587-4731

TITLE	DATE
CONNECTION DIAGRAM	4/20/2023
NAME: EXHAUST ONLY - EBC 31 & RSV 400-450	JOB # Generic
DWG BY: YKH	SHEET: 1 OF 2
	REV # 0