



Fan		EDRIVE				MOTOR	
Model	Voltage (V)	ITEM #	INPUT VOLTAGE	OUTPUT VOLTAGE (V)	MAX INPUT CURRENT (A)	NOT FIELD ADJUSTABLE	FIELD ADJUSTABLE
EFV 250	3X 208 -240	321.2306.2200	3X200-240	3X200-240	3.3	200V DELTA	~
	3X 208 -240	321.2308.2200	3X200-240	3X200-240	6.5	~	200V (DELTA)
EFV 315	3X 380-480	321.2308.4200	3X380-480	3X380-480	3.7	~	400V (WYE)
	3X 208 -240	321.2311.2200	3X200-240	3X200-240	6.5	~	200V (DELTA)
EFV 400	3X 380-480	321.2311.4200	3X380-480	3X380-480	3.7	~	400V (WYE)
	3X 208 -240	321.2313.2200	3X200-240	3X200-240	6.5	~	200V (DELTA)
EFV 450	3X 208 -240	321.2313.2200	3X200-240	3X200-240	6.5	~	200V (DELTA)
	3X 380-480	321.2313.4200	3X380-480	3X380-480	3.7	~	400V (WYE)

Note:

The wire sizes shown are typical and may not apply to all jobs. This system must be installed in compliance with the NFPA 70 National Electric Code and/or any local codes.

— Line Voltage

----- Low Voltage Signal

PROPRIETARY AND
CONFIDENTIAL
The information contained in this
drawing is the sole property of
ENERVEX, Inc. Any reproduction in
part or as a whole with out the
express written consent of
ENERVEX, Inc. is prohibited.

NOT TO SCALE

ENERVEX®
GREEN BEFORE GREEN WAS IN

1685 Bluegrass Lakes Pkwy
Alpharetta, GA 30004
(770)587-3238
Fax (770)587-4731

TITLE	CONNECTION DIAGRAM	DATE	9/15/2023
NAME	EXHAUST ONLY - EBC 31 & EFV 400-450	JOB #	Generic
DWG BY	YKH	SHEET	1 OF 2
REV			# 1